

Spohn Performance, Inc.

494 E Lincoln Ave Myerstown, PA 17067
1-888-365-6064 www.spohn.net

Part# F5-M34-205 Factory Five MK3 & MK4 with Solid Rear Axle Adjustable Rear Lower Control Arms – Del-Sphere™ Pivot Joints

USE OF THIS PRODUCT IS ACCEPTANCE OF SELLER'S DISCLAIMER OF WARRANTY!

By their very nature, competition components are constantly pushed to their limits. While our components are designed to withstand intense race conditions, it is impossible to control the quality of installation or the varying conditions in which they are used. It is for this reason that absolutely no warranty or guarantee is either written or implied. Neither the seller nor the manufacturer will be liable for any loss, damage, or injury – direct or indirect – arising from the use of or inability to determine the use of any product. Before using, the user should determine the suitability of the product for its intended use, and the user shall assume all responsibility in connection therewith. Spohn Performance, Inc. makes no guarantee as to the legality for any specific class. Spohn Performance, Inc. makes no claims, nor does it intend its products to be used in street driven vehicles. Spohn Performance, Inc. reserves the right to make changes in design or add to or improve on their product without incurring any obligation to install the same on product previously manufactured. The Buyer agrees to indemnify and hold Spohn Performance, Inc. harmless from any claim, action or demand arising out of or incident to the Buyer's installation or use of products purchased from Spohn Performance, Inc.

INSTRUCTIONS

1. Lift rear of vehicle and support by frame rails. DO NOT SUPPORT BY REAR END!
2. Use jack and place under rear axle to support but do not lift.
3. Remove both the front and the rear lower control arm bolts and nuts and remove the rear lower control arm. The axle will shift slightly rearward. (Remove and replace one LCA at a time)
4. Install control arms using the jack to help position the rear axle properly. Use the supplied spacers on either side of the Del-Sphere™ ends. Make the bolts hand tight only at this time. If the spacers are a tight fit, simply sand them down until they fit. (The LCAs ship with the bushing and spacers wire tied in place so you know how they are to be installed).
5. Safely lower vehicle to the ground and then tighten all bolts to 72 ft/lbs.
6. One end of the LCA is left hand threaded and the other end is right hand threaded. To adjust the length of your LCAs simply put a wrench on the hex at the end of the LCA and turn the LCA clockwise or counter-clockwise to lengthen or shorten the LCA. This will allow you to push your rear front/back.
7. Jam nuts are known to work loose over time. To prevent this we recommend that after you have the LCAs set to your desired length you apply some REMOVABLE strength (Blue) Loctite to the Del-Sphere™ threads and then tighten up the jam nuts on each end of the lower control arm. **Note:** The LCAs are shipped to you jig set at stock length.

Del-Sphere™ Pivot Joint Instructions & Notes

The Del-Sphere™ pivot joints are slightly greased for assembly purposes. The bushings inside of the Del-Sphere™ pivot joints are made of Delrin, which is self-lubricating. We do not recommend greasing the pivot joint any further than as it is supplied as further grease will only attract and retain dirt and grit. The pivot joints are equipped with grease fittings simply because we know certain customers would want/request them no matter what we say.

Our Del-Sphere™ pivot joints are 100% rebuild-able. We doubt you will ever need to rebuild them, but they certainly can be. The Delrin bushings should last the life of your vehicle. What you may find is after you have a lot of miles on the pivot joints the tolerances may slightly open. It is for this reason that we made the pivot joints adjustable. By tightening the threaded end retainer you can take up any slack and make the joint as tight as it was when new, it's that simple. This also allows you to vary the torque load applied to the pivot ball. If you want a very low friction joint you can loosen the threaded end retainer, etc. When making adjustments to the threaded end retainer you will need to loosen the set screw with an allen wrench. When making your adjustment align one of the threaded retainer end's slots with the set screw and re-tighten the set screw, this locks the threaded end retainer's position in to place and keeps it locked to your setting. Use our Part# **DS34-W** adjusting tool for easy adjustments.

What is a Del-Sphere™ pivot joint? Think of the Del-Sphere™ pivot joint as a Delrin bushed spherical rod end. Designed and manufactured exclusively by Spohn Performance, we have taken suspension performance to the next level. Our Del-Sphere™ pivot joint features either a one piece forged and heat treated chrome moly housing or a CNC machined 1020 DOM housing (weldable version), a heat treated and hard chrome plated chrome moly spherical ball, Delrin bushing races, heat treated retainer washer and snap ring, heat treated and zinc plated chrome moly threaded adjuster ring, an external grease fitting and a beautiful silver zinc plated housing finish. The Delrin bushing races absorb shock and road noise so you get the quiet and smooth ride of a bushing as well as **28 degrees of rotation!**

What is Delrin, and why did you choose to use it? Delrin is an acetal homopolymer made by DuPont. It is characterized as having an excellent combination of physical properties that make it suitable for numerous applications. With extremely low moisture absorption and a low coefficient of friction (self-lubricating), Delrin is uniquely tailored for wear applications in high humidity or moisture environments. Delrin will maintain constant physical properties under high moisture conditions and out-perform nylon or polyurethane under these conditions. Delrin has a 10,000 psi tensile strength and a 120 Rockwell Hardness rating making it ideal for our Del-Sphere™ pivot joint application.

Replacement Parts:

Part #	Description
DS34RH	Forged Del-Sphere™ Assembly - 3/4"-16 RH x 3/4" Bore
DS34LH	Forged Del-Sphere™ Assembly - 3/4"-16 LH x 3/4" Bore
DS34B-225	2.25" O.D. x 0.200" Wall 1020 DOM Weldable Del-Sphere™ Assembly
DS34B-250	2.50" O.D. x 0.325" Wall 1020 DOM Weldable Del-Sphere™ Assembly
DS34-W	Del-Sphere™ Adjustment Tool
DS34-Wash	Del-Sphere™ End Washer
DS34-TE	Del-Sphere™ Threaded Adjuster End
DS34-SR	Del-Sphere™ Snap Ring
DS34-Bush	Del-Sphere™ Delrin Bushing (2 per assembly)
DS34-Ball	Del-Sphere™ Hard Chrome Plated Spherical Ball